



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277

spa.mumbai@kei-ind.com



PRICE LIST : 6th MAY 2022

LP NO. KEI/W&F/LP/22-23/01 DT.06.05.2022

INDUSTRIAL MULTI STRAND CABLES

HSN CODE : 85.44.60.20

KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1020	28	2040	12	11.33
0.75	24/0.20	7	1370	28	2740	12	15.22
1.00	32/0.20	11	1800	24	3600	12	20.00
1.50	30/0.25	14	2630	16	5260	8	29.22
2.50	50/0.25	19	4220	12	8440	6	46.89
4.00	56/0.30	26	6240	8	12480	4	69.33
6.00	84/0.30	31	9470	6	18940	3	105.22
10.00	80/0.40	42	16860	1			187.33
16.00	126/0.40	57	26270	1			291.89

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1110	28	2220	12	12.33
0.75	24/0.20	7	1410	28	2820	12	15.67
1.00	32/0.20	11	1880	24	3760	12	20.89
1.50	30/0.25	14	2750	16	5500	8	30.56
2.50	50/0.25	19	4430	12	8860	6	49.22
4.00	56/0.30	26	6540	8	13080	4	72.67
6.00	84/0.30	31	9900	6	19800	3	110.00
10.00	80/0.40	42	17650	1			196.11
16.00	126/0.40	57	27570	1			306.33

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1490	28	2980	12	16.56
1.00	32/0.20	11	2010	24	4020	12	22.33
1.50	30/0.25	14	2880	16	5760	8	32.00
2.50	50/0.25	19	4570	12	9140	6	50.78
4.00	56/0.30	26	6640	8	13280	4	73.78
6.00	84/0.30	31	10040	6	20080	3	111.56
10.00	80/0.40	42	18060	1			200.67
16.00	126/0.40	57	28060	1			311.78

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7th Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277
spa.mumbai@kei-ind.com



PRICE LIST : 6th MAY 2022

LP NO. KEI/W&F/LP/22-23/01 DT.06.05.2022

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES

HSN CODE : 85.44.60.20

KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR 105 Deg	SINGLE CORE FRLSH
0.5	16/0.20	4	24	1130	1210	1220	35	276/0.4	110	64510	66660	67650
0.75	24/0.20	7	24	1520	1550	1565	50	396/0.4	145	93850	95230	96040
1.0	32/0.20	12	20	2000	2080	2090	70	354/0.5	200	131520	133430	134430
1.5	30/0.25	16	16	2920	3050	3055	95	484/0.5	235	173230	176750	178060
2.5	50/0.25	22	12	4690	4900	4920	120	608/0.5	270	221530	225450	228400
4.0	56/0.30	29	8	6935	7220	7265	150	750/0.5	310	277610	282600	284720
6	84/0.30	37	4	10520	10950	11000	185	925/0.5	360	336460	343120	345980
10	80/0.40	51	1	18730	19430	19610	240	1210/0.5	425	444140	452490	456970
16	126/0.40	68	1	29190	30610	30630	300	1527/0.5	490	553540	563550	569550
25	196/0.40	86	1	46180	47750	48440	400	2036/0.5	590	732790	735040	741730

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	3440	4540	5650	7680	8890	9700	15060	17390	19830	22630	26140	33440
0.75	24/0.20	4670	5960	7680	10590	12080	13340	20280	23560	27210	31000	36000	45990
1.0	32/0.20	5200	7100	9330	12330	14650	16440	24910	28800	33280	37970	44000	56100
1.5	30/0.25	7100	9910	12810	17220	20170	22610	33620	39560	45820	52320	60790	77800
2.5	50/0.25	11510	15950	20900	27310	32280	36050	53250	63040	73730	83720	98010	125140
4.0	56/0.3	17940	25950	33390	44810	51340	59480	87520	103770	120360	136940	160830	206680
6	84/0.3	26440	37590	50130	64530								
10	80/0.4	44210	63450	83730	109260								
16	126/0.4	68090	97540	128750									
25	196/0.4		156990	206070									
35	276/0.4		218300	284680									
50	396/0.4		312620	408670									
70	354/0.5		431390	567630									
95	484/0.5		0	751050									
120	608/0.5												

Note :

KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	10190
2.5	50/0.25	15770
4	56/0.3	23440
6	84/0.3	34900
10	80/0.4	58760
16	126/0.4	92850
25	196/0.4	139560

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.