


PRICE LIST : 26th JUL 2022
LP NO. KEI/W&F/LP/22-23/05 DT.26.07.2022
INDUSTRIAL MULTI STRAND CABLES
HSN CODE : 85.44.60.20
KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	920	28	1840	12	10.22
0.75	24/0.20	7	1230	28	2460	12	13.67
1.00	32/0.20	11	1620	24	3240	12	18.00
1.50	30/0.25	14	2370	16	4740	8	26.33
2.50	50/0.25	19	3800	12	7600	6	42.22
4.00	56/0.30	26	5630	8	11260	4	62.56
6.00	84/0.30	31	8540	6	17080	3	94.89
10.00	80/0.40	42	15200	1			168.89
16.00	126/0.40	57	23680	1			263.11

KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1000	28	2000	12	11.11
0.75	24/0.20	7	1270	28	2540	12	14.11
1.00	32/0.20	11	1700	24	3400	12	18.89
1.50	30/0.25	14	2480	16	4960	8	27.56
2.50	50/0.25	19	3990	12	7980	6	44.33
4.00	56/0.30	26	5890	8	11780	4	65.44
6.00	84/0.30	31	8940	6	17880	3	99.33
10.00	80/0.40	42	15910	1			176.78
16.00	126/0.40	57	24860	1			276.22

KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1350	28	2700	12	15.00
1.00	32/0.20	11	1800	24	3600	12	20.00
1.50	30/0.25	14	2600	16	5200	8	28.89
2.50	50/0.25	19	4120	12	8240	6	45.78
4.00	56/0.30	26	5990	8	11980	4	66.56
6.00	84/0.30	31	9040	6	18080	3	100.44
10.00	80/0.40	42	16280	1			180.89
16.00	126/0.40	57	25300	1			281.11

Notes:

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.


PRICE LIST : 26th JUL 2022
LP NO. KEI/W&F/LP/22-23/05 DT.26.07.2022
PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES
HSN CODE : 85.44.60.20
KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR	SINGLE CORE FRLSH
0.5	16/0.20	4	24	1020	1100	1110	35	276/0.4	110	58170	60100	60990
0.75	24/0.20	7	24	1365	1400	1410	50	396/0.4	145	84610	85850	86600
1.0	32/0.20	12	20	1800	1870	1890	70	354/0.5	200	118570	120290	121190
1.5	30/0.25	16	16	2635	2750	2755	95	484/0.5	235	156180	159350	160540
2.5	50/0.25	22	12	4220	4410	4435	120	608/0.5	270	199730	203260	205920
4.0	56/0.30	29	8	6255	6510	6545	150	750/0.5	310	250280	254790	256700
6	84/0.30	37	4	9490	9880	9935	185	925/0.5	360	303340	309350	311930
10	80/0.40	51	1	16890	17520	17680	240	1210/0.5	425	400430	407960	411990
16	126/0.40	68	1	26310	27600	27620	300	1527/0.5	490	499050	508090	513490
25	196/0.40	86	1	41630	43050	43680	400	2036/0.5	590	660660	662690	668730

KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	3090	4090	5090	6930	8020	8740	13570	15680	17870	20400	23570	30150
0.75	24/0.20	4210	5370	6930	9550	10900	12030	18280	21250	24540	27940	32450	41460
1.0	32/0.20	4690	6400	8410	11120	13200	14820	22460	25970	30010	34240	39670	50580
1.5	30/0.25	6400	8950	11540	15520	18180	20380	30310	35660	41310	47170	54800	70140
2.5	50/0.25	10370	14380	18840	24610	29100	32500	48010	56830	66470	75480	88360	112830
4.0	56/0.3	16180	23400	30110	40400	46280	53620	78900	93560	108510	123450	145000	186340
6	84/0.3	23840	33890	45200	58180								
10	80/0.4	39850	57210	75490	98510								
16	126/0.4	61390	87940	116080									
25	196/0.4		141540	185800									
35	276/0.4		196820	256660									
50	396/0.4		281840	368450									
70	354/0.5		388930	511760									
95	484/0.5		0	677120									
120	608/0.5												

Note :
KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	9190
2.5	50/0.25	14210
4	56/0.3	21130
6	84/0.3	31460
10	80/0.4	52980
16	126/0.4	83720
25	196/0.4	125810

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
 - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
 - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
 - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
 - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
 - Single Core 10sqmm and above will be supplied in single coil packing.
 - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.