


**PRICE LIST : 16<sup>th</sup> NOV 2022**
**LP NO. KEI/W&F/LP/22-23/06 DT.16.11.2022**
**INDUSTRIAL MULTI STRAND CABLES**
**HSN CODE : 85.44.60.20**
**KEI HOMECAB - FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES - FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	950	28	1900	12	10.56
0.75	24/0.20	7	1270	28	2540	12	14.11
1.00	32/0.20	11	1670	24	3340	12	18.56
1.50	30/0.25	14	2440	16	4880	8	27.11
2.50	50/0.25	19	3910	12	7820	6	43.44
4.00	56/0.30	26	5800	8	11600	4	64.44
6.00	84/0.30	31	8800	6	17600	3	97.78
10.00	80/0.40	42	15660	1			174.00
16.00	126/0.40	57	24390	1			271.00

**KEI CONFLAME - FRLSH PVC INSULATED INDUSTRIAL SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES WITH FLAME RETARDANT LOW SMOKE (FRLSH) PROPERTIES, WITH FLEXIBLE BRIGHT ANNEALED BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.50	16/0.20	4	1030	28	2060	12	11.44
0.75	24/0.20	7	1310	28	2620	12	14.56
1.00	32/0.20	11	1750	24	3500	12	19.44
1.50	30/0.25	14	2550	16	5100	8	28.33
2.50	50/0.25	19	4110	12	8220	6	45.67
4.00	56/0.30	26	6070	8	12140	4	67.44
6.00	84/0.30	31	9210	6	18420	3	102.33
10.00	80/0.40	42	16390	1			182.11
16.00	126/0.40	57	25610	1			284.56

**KEI BANFIRE - SINGLE CORE, UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - ZERO HALOGEN FLAME RETARDANT (ZHFR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V.**

CONDUCTOR (AREA SQ.MM)	NO. & SIZE OF WIRE IN MM	CURRENT (AMPS) BUNCHED & ENCLOSED IN CONDUIT OR TRUNKING	RATE PER 90M COIL	STANDARD PACKING FOR 90MTR.	RATE PER 180M COIL	STANDARD PACKING FOR 180MTR.	RATE PER MTR
0.75	24/0.20	7	1390	28	2780	12	15.44
1.00	32/0.20	11	1850	24	3700	12	20.56
1.50	30/0.25	14	2680	16	5360	8	29.78
2.50	50/0.25	19	4240	12	8480	6	47.11
4.00	56/0.30	26	6170	8	12340	4	68.56
6.00	84/0.30	31	9310	6	18620	3	103.44
10.00	80/0.40	42	16770	1			186.33
16.00	126/0.40	57	26060	1			289.56

**Notes:**

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.
- Standard colours in Building wires are RED / BLACK / BLUE / YELLOW / GREEN.
- FR / FRLSH & ZHFR wires are supplied in standard lengths of 90M Coils & 180M Coils packed in Master Cartons.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- For other Colours or Lengths please contact our Marketing Department.
- This Price List is subject to change without prior notice.



# KEI INDUSTRIES LIMITED (MUMBAI)

Nirvan Corporate, 7<sup>th</sup> Floor, Opp. Aghadi Nagar, Andheri Pump House, Andheri - East,  
Mumbai - 400 093. Tel. : 022-2837 5642 / 2823 9673 Fax : 2825 8277  
spa.mumbai@kei-ind.com



PRICE LIST : 16<sup>th</sup> NOV 2022

LP NO. KEI/W&F/LP/22-23/06 DT.16.11.2022

PVC INSULATED INDUSTRIAL FLEXIBLE SINGLE & MULTI CORE CABLES

HSN CODE : 85.44.60.20

**KEI FLEXIBLE FR PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL MULTISTRAND CABLES FLAME RETARDANT (FR) WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

(Rate in Rs. Per 100 Mtrs)

SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	STD. PACK OF 100 MTR COIL	SINGLE CORE FR	SINGLE CORE HRFR	SINGLE CORE FRLSH	SQ.MM	COND. CONST. (NO./DIA. MM)	CURRENT (AMPS) CLIPPED DIRECT TO A SURFACE OR ON A CABLE TRAY, BUNCHED & UNENCLOSED	SINGLE CORE FR	SINGLE CORE HRFR	SINGLE CORE FRLSH
0.5	16/0.20	4	24	1050	1130	1140	35	276/0.4	110	59920	61900	62820
0.75	24/0.20	7	24	1410	1440	1455	50	396/0.4	145	87150	88430	89200
1.0	32/0.20	12	20	1855	1930	1945	70	354/0.5	200	122130	123900	124830
1.5	30/0.25	16	16	2710	2830	2835	95	484/0.5	235	160870	164130	165360
2.5	50/0.25	22	12	4345	4540	4565	120	608/0.5	270	205720	209360	212100
4.0	56/0.30	29	8	6445	6710	6745	150	750/0.5	310	257790	262430	264400
6	84/0.30	37	4	9780	10180	10235	185	925/0.5	360	312440	318630	321290
10	80/0.40	51	1	17400	18050	18210	240	1210/0.5	425	412440	420200	424350
16	126/0.40	68	1	27100	28430	28460	300	1527/0.5	490	514020	523330	528890
25	196/0.40	86	1	42880	44340	44990	400	2036/0.5	590	680480	682570	688790

**KEI FLEXIBLE PVC INSULATED MULTICORE FR PVC SHEATHED MULTISTRANDED CABLES WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE UPTO 1100 V CONFORMING TO IS-694:2010.**

SQ.MM	COND. CONST. (NO./DIA.MM)	2 CORE	3 CORE	4 CORE	5 CORE	6 CORE	7 CORE	10 CORE	12 CORE	14 CORE	16 CORE	19 CORE	24 CORE
0.5	16/0.20	3180	4210	5240	7140	8260	9000	13980	16150	18410	21010	24280	31050
0.75	24/0.20	4340	5530	7140	9840	11230	12390	18830	21890	25280	28780	33420	42700
1.0	32/0.20	4830	6590	8660	11450	13600	15260	23130	26750	30910	35270	40860	52100
1.5	30/0.25	6590	9220	11890	15990	18730	20990	31220	36730	42550	48590	56440	72240
2.5	50/0.25	10680	14810	19410	25350	29970	33480	49450	58530	68460	77740	91010	116210
4.0	56/0.3	16670	24100	31010	41610	47670	55230	81270	96370	111770	127150	149350	191930

6	84/0.3	24560	34910	46560	59930	
10	80/0.4	41050	58930	77750	101470	
16	126/0.4	63230	90580	119560		
25	196/0.4		145790	191370		
35	276/0.4		202720	264360		
50	396/0.4		290300	379500		
70	354/0.5		400600	527110		
95	484/0.5		0	697430		
120	608/0.5					

**Note :**

**KEI 3 CORE FLAT CABLES FOR SUBMERSIBLE PUMP MOTORS**

(Rate in Rs. Per 100 Mtrs)

SQ. MM	COND. CONST. (NO./DIA.MM)	RATE
1.5	30/0.25	9470
2.5	50/0.25	14640
4	56/0.3	21760
6	84/0.3	32400
10	80/0.4	54570
16	126/0.4	86230
25	196/0.4	129580

- FRLS Loading - 3% Extra for Multi Core Flexible Cables.**
- KEI 3 Core Flat Submersible Cables PVC Insulated & Sheathed with XLPE can be supplied at the same rates as PVC insulated cables.
- Packing for 3 Core Flat Submersible Cables :**
  - Cables upto 4sqmm are supplied in 500Mtr/1000Mtr drums.
  - Cables from 6sqmm to 25sqmm are supplied in 500Mtr drums.
  - Cables of 1.5sqmm, 2.5sqmm & 4sqmm are also supplied in 300Mtr coil.
- Packing for Single & Multi Core Round Wire Flexible cables :**
  - Single Core Flexible cables upto 6sqmm are supplied in Master Carton as shown above.
  - Single Core 10sqmm and above will be supplied in single coil packing.
  - Single Core 120sqmm and above & Multicore 6sqmm & above available in coil packing.

- GST and any other tax/levy will be charged extra, at actuals. Freight as per Policy.
- Please refer to our Marketing Department for Wires & Cables, not covered above.
- This Price List is subject to change without prior notice.